



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(57) International Patent Classifications: A61M 15/00	A1	(51) International Publication Number: WO 99/36116	NO 99/36116 23 July 1999 (23.07.99)
(31) International Application Number: PCT/US99/00028			
(32) International Filing Date: 15 January 1999 (15.01.99)			
(33) Priority Data: 1008031 15 January 1998 (15.01.98)	NL		
(71) Applicant (as all designated States except US): PHARMACHEMIS B.V., Dijkshoek 3, NL-3023 GA Rotterdam (NL)			
(72) Inventor(s) and (73) Invention/Applicant (as US only): VAN GEDEKKE, Wilhelmus, Marja [NL/NL]; Dr. Brummens 14, NL-1506 KN Amstelveen [NL/NL]; NUTZEL, Alfred, James [NL/NL]; Wierhorst Wierhorste 17, NL-10177 ZJ Amsterdam [NL/NL]; SANDERS, Johannes, Wilhelmus, Marja [NL/NL]; Lankster 40, NL-2135 DE Rindshout [NL/NL]; Smit, Janes [NL/NL]; Grahsmann 23, NL-1775 GF Helsum [NL]			
(74) Agent: ARNOLD & STEDMAN, Lund, Adolph Axelsson Gullström, Sveablicksgården 1, SE-2517 OX The Hague (NL)			
(54) Title: DEVICE FOR INHALING MEDICATION			
(57) Abstract			
<p>The present invention comprises a device for inhaling medication, comprising: a first housing part provided with one or more cavities in which a dose of a pre-determined quantity of medication can be arranged; and a second housing part which is fixed substantially non-adjustably to the first housing part, wherein the first and second housing parts are movable relative to one another between a first position wherein the cavity with premeasured medication are closed and a second position in which the cavity is placed into connection with an air path and the medication can be inhaled.</p>			

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify those entry to the PCT as the first phase of applicants publishing international application under the PCT

AL	Albanian	33	Stale	13	Lebanese	25	Dominican
AM	American	17	Mexican	17	Lithuanian	25	Slavonic
AT	Austrian	19	Polish	17	Lombardian	25	Southern
CA	Canadian	27	Portuguese	17	Lotharingian	25	Swedish
EA	English	33	Quebec French	30C	Macedonian	19	Choi
ES	Spanish and Portuguese	33	Quebec	30C	Magyar of Hungary	19	Choi
EU	European	33	Quebec	30C	Magyar of Hungary	19	Choi
FR	French	33	Quebec	30C	Magyar of Hungary	19	Choi
GE	Georgian	33	Quebec	30C	Magyar of Hungary	19	Choi
GR	Greek	33	Quebec	30C	Magyar of Hungary	19	Choi
HA	Haitian	33	Quebec	30C	Magyar of Hungary	19	Choi
HE	Hebrew	33	Quebec	30C	Magyar of Hungary	19	Choi
HO	Hungarian	30	Magyar	30C	Magyar of Hungary	19	Choi
IR	Irish	33	Irish	30C	Magyar of Hungary	19	Choi
IT	Italian	33	Irish	30C	Magyar of Hungary	19	Choi
JA	Japanese	17	Italy	30C	Magyar of Hungary	19	Choi
KE	Korean	27	Niger	30C	Magyar of Hungary	19	Choi
LE	Latvian	33	Europe	30C	Magyar of Hungary	19	Choi
LI	Lithuanian	33	European People's	30C	Magyar of Hungary	19	Choi
LO	Lotharingian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MA	Macedonian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MC	Magyar	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
ME	Mexican	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MI	Michigan	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MO	Moldavian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MP	Montenegrin	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MS	Maltese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
MT	Maltese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NA	Norwegian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NE	Nepalese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NI	Niger	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NO	Norwegian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NP	Nepalese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NS	Norwegian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NT	Norwegian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
NU	Norwegian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
OV	Old Norse	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PA	Pakistani	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PE	Peruvian	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PF	Polish	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PG	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PH	Philippine	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PI	Pakistani	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PL	Polish	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PM	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PN	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PO	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PP	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PR	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PS	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PT	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PU	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PV	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PW	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PX	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PY	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
PZ	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QA	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QB	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QC	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QD	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QE	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QF	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QG	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QH	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QI	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QJ	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QK	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QL	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QM	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QN	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QO	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QP	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QQ	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QR	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QS	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QT	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QU	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QV	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QW	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QX	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QY	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi
QZ	Portuguese	33	Magyar of Hungary	30C	Magyar of Hungary	19	Choi

WO 99/36116

PCT/01/39/00029

970 7936116

3

PCT/AL92/00023

DEVICE FOR INHALABLE MEDICATIONS

Devices for inhaling medication, for instance for asthma patients, are very common nowadays. Already known are so-called multi-dose inhalers, wherein one powdered (or liquid) dose at a time is transported from a reservoir to a mixing space, whereafter, after suction, the medication reaches the bronchial tubes of the user via the mouth. Inhaler devices further exist wherein one or more doses arranged in a blister pack are placed in a device, whereafter the medication can be inhaled after piercing of the blister pack. It is also known to inhale from an inhaler device the content of a capsule which must first be pierced or divided.

From the American patent specification 5,622,166 an inhaler device is known wherein a disc-shaped blister pack is rotated each time and 15 perforated by a pin which can be operated by a coil spring. This construction is relatively complicated and expensive and is not suitable as disposable inhaler device; only the blister pack is discarded.

20 The present invention has for its object to provide a disposable inhaler device which can be manufactured in large numbers at relatively low cost price; the dimensions thereof can remain extremely small, so that the user can readily take along one or more of 25 such inhaler devices and throw them away after use.

The present invention provides a device for inhaling medication, comprising:

- a first housing part provided with one or more cavities in which a dose of a pre-determined quantity of medication can be arranged; and
- a second housing part which is fixed substantially non-releasably to the first housing part.

wherein the first and second housing parts are movable relative to one another between a first position wherein the cavities with powdered medication are closed and a second position in which the interior of one of the 3 cavities is placed in connection with an air path and the medication can be inhaled.

In a first preferred embodiment the movable part is rotatable, wherein a number of cavities for the medication for dispensing is accommodated in the rotatable part. It is however also conceivable for the first and second housing parts to be mutually slidable. The rotatable part is preferably rotatable in one direction and a clear click is audible and can be clearly felt as soon as a dose is rotated to the dispensing position. If the rotatable part is accidentally revolved too far without a dose being inhaled, this dose is again closed off from the environment with further rotation. Since in the preferred embodiment the device is blocked after the last dose has been rotated into the air path, a dose which has been revolved too far further remains inaccessible.

In a further preferred embodiment the device is enclosed by a liquid-tight and/or airtight packaging in order to prevent the medication becoming moist (and possibly lumpy) and/or losing its activity over a longer period of time. On this outer wrapper can be further arranged information relevant to the product and it also serves as guarantee for the user that the device is definitely safe and has not been used before. A number of devices according to the present invention can also be arranged in a blister-type packaging.

The number of doses can amount to one, for instance in the case of morphine, but can also amount to four or more, for instance sufficient for use in one

Further preferred embodiments solve the problem of inept use of an inhaler device according to the present invention; closing means are for instance

provided herein for closing off a dose of medication so that it cannot fall out of the device without being inhaled when this latter is upside down, and/or blocking means for blocking the mutual rotation movement in upside down position of the device.

Further advantages, features and details of the present invention will be elucidated on the basis of the following description of a preferred embodiment thereof with reference to the annexed drawings, in which:

10 fig. 1 shows an isometric bottom view of a preferred embodiment of a device according to the present invention;

fig. 2 shows an isometric top view of the preferred embodiment shown in fig. 1;

15 fig. 3 is a top view of a component of the preferred embodiment shown in fig. 1 and 2;

fig. 4 shows a disassembled view of the device shown in fig. 1 and 2, wherein the component of fig. 3 is filled with medication;

20 fig. 5 is a view in cross-section along the line V-V of fig. 2;

fig. 6 shows a partly broken-away perspective view of a further preferred embodiment of the device according to the present invention;

25 fig. 7A and 7B show respective partly broken-away views of a further preferred embodiment of a device according to the present invention in a first respectively second position;

fig. 8 is a partly broken-away perspective view of a further preferred embodiment of a device according to the present invention;

fig. 9 shows a partly broken-away perspective view of a further preferred embodiment according to the present invention;

35 fig. 10 is a partly broken-away perspective view of a further preferred embodiment according to the present invention;

In another preferred embodiment (not shown) a suction opening can also be arranged in the bottom in order to further reduce the air resistance and to prevent the air resistance becoming too great if the user should accidentally place a finger on one of the two suction openings.

As shown clearly in fig. 3, the part 12 is provided with a protrusion 14 for the counting mechanism, while it is further provided with cavities 16, 17, 18 and 19 for receiving powdered medication preferably poured therein. In addition to cavities 16-19, recesses 21, 22, 23, 24 and 25 are arranged for strengthening the structure, saving plastic material and preventing moisture from entering cavities 16-19. Arranged around a blind hole 30 are obliquely rising wall parts 26, 27, 28 and 29, each co-acting with flexible wall part 7 on housing part 10 during rotation thereof, wherein protruding part 14 co-rotates. A gap 32 is shown in fig. 4 adjacently of flexible wall part 7.

20 After cavities 16, 17, 18 and 19 have been filled with inhalable powder, housing part 10 is locked in snapping manner on lower housing part 12 such that in practice the device cannot be opened by the user. After the snap connection the device is situated in the neutral position or starting position shown in fig. 2, wherein protrusion 14 indicates that four doses are still available. If the user wishes to inhale a dose, the lower housing part 12 is rotated, wherein flexible wall part 7 rotates along the protruding wall part 26 and falls between wall parts 26 and 27 with a clicking sound which can also be felt. In this situation (and in the case of subsequent rotation between the other markings shown in fig. 2) an air path is left clear over the relevant cavity and the powder is carried out of the cavity into the mouthpiece by the underpressure generated by the airflow.

Fig. 5 further shows clearly that the upper part has a substantially conical surface, which connects

fig. 11 is a partly broken-away perspective view of a further preferred embodiment according to the present invention;

fig. 12 is a partly broken-away perspective view of a further preferred embodiment according to the present invention; and

fig. 13 shows a partly broken-away perspective view of a further preferred embodiment according to the present invention.

10 A device 1 (fig. 1-5) is preferably packed in a packaging 2 which is in any case (water-) vapour-tight but preferably also airtight, such as a blister pack, a foil 3 of which can be pulled off a short time before use. Device 1 further comprises a mouthpiece 4 which is provided on the top side with a raised edge 5 in order to ensure that the device is inserted to the correct distance, but not too far, into the mouth. In an embodiment which is not shown, the device can be arranged in a blister-type packaging in which for instance four or six devices are included, of which one at a time can then be pressed through the blister pack.

Mouthpiece 4 is preferably formed integrally with a housing part 10 (see in particular fig. 4) and comprises a central bush 6 with a slightly flexible wall 7 part 7 which is separated from wall part 7 via gap 32, one of which is visible. Situated on the top side is a suction opening 9 with ribs 11 extending thereover. When the air is sucked in for instance at a minimum quantity of 20 litres per minute, the air moving over the cavity 30 is drawn in and the powder from the cavity is carried along by the airflow. In the shown preferred embodiment the air resistance is moderate, i.e. a user with low sucking power can also draw the powder from the cavity. On the top the component 10 is preferably further provided with markings (4, 3, 2 respectively 1) indicating the number of doses still to be inhaled. A lower housing part 12, preferably provided with gripping surfaces 13, is rotatable relative to housing part 10.

onto a conical surface on the lower part situated beneath a snap edge. Between the upper and the lower part a minimal distance (d) is left clear so as to avoid problems in respect of the tolerances in the applied injection moulding technique; use is preferably made of a high-grade, injection-mouldable plastic which can for instance be re-used for other purposes.

As shown particularly in fig. 3, when in the shown preferred embodiment the flexible wall part arrives in the end position between the standing end portions of edge parts 29 and 31, in which position the device is blocked against further rotation, the user knows that the inhaler can be discarded, which is indicated by the counting mechanism which no longer points to a number of still available doses.

After rotating the disc the user can easily suck on the device according to the present invention, this requiring a comparatively simply hand-mouth coordination. In addition, a dosage of medication (for some medicines with addition of carrier material (such as lactose)) is preferable dispensed in the cavities such that the user feels in mouth and throat cavities that inhalation has taken place.

In a second preferred embodiment of a device 40 (fig. 6) according to the present invention, component 44 is provided for the purpose of strengthening the ratchet mechanism with two pawls 47 and 48, of which pawl 48 is partly broken away in fig. 6 and which both fall into the recesses between inclining protrusions 45, 46, four of which are arranged on component 42 in this embodiment with four dosages.

The blocking or end stop after inhaling of the final dose then preferably takes place by means of protrusion 49, which also indicates the number of doses still to be used and, after the final dose, falls in a manner not shown into a recess on the outside of component 42 or clamps against the mouthpiece of component 44.

In order to prevent mutual rotation of components 42 and 44 taking place in the upside down position of device 40, a blocking element 51 is arranged in a recess 50 in component 42, which element, in the case of reversal as according to arrow A, will drop due to its own weight into a respective recess 52 in component 44 which has a smaller depth than recess 50 such that rotation is then blocked. The number of recesses in component 44 will correspond to the number of cavities in which medicinal powder is received. It will be apparent that it is possible to suffice with one cavity when the blocking element is centrally arranged in the point of rotation.

In the embodiment according to fig. 7A and 7B, which is provided for instance with seven doses of powder for inhaling, the medicine is only released when inhalation takes place. In the device 60 a valve 61 blocking the airflow is arranged pivotally on a shaft 62, while in the position of valve 61 shown in fig. 7A, wherein the airflow is blocked, the dose of medicine is covered using a slidable valve element 64.

In the case of (gentle) inhalation, as indicated with arrows B respectively C in fig. 7B, valve 61 pivots on shaft 62 and slide valve 64 is displaced in the direction of arrow D, so that dose d is released and can be inhaled. Slide valve 64 displaces for instance under the influence of a spring element, the force of which in the direction of arrow D is checked in closed position of valve 61, for instance using a finger. When disc 63 is rotated to the following dose, slide 64 is moved back to the position closing off the following dose.

If the preferred embodiment of fig. 8 is held upside down while a dose e is in open communication with mouthpiece 71, this powder will fall into a collecting space 72 formed on mouthpiece 71, while on the inside of suction part 71 a rib 73 is further arranged which forms

a barricade preventing medicinal powder from falling out of the inhaler device.

Because in device 70 as according to fig. 8 the air supply opening 74 is situated in the correct position on the underside, the powder will not be able to leave the device therethrough in the reversed position.

In the embodiment 80 of fig. 9 of a device according to the present invention, a cylindrical part 82 is placed in the air inlet part 83 close to the centre of disc 81. A closing lip 84 is fixed to the tube 82. During inhaling the closing lip 84 is lifted by the airflow and an opening is left clear through which the powder can be inhaled by suction over the cavity in which the medicinal powder is situated. It is possible in a manner not shown to provide device 80 with a spring element to force back the cylindrical part. In another preferred embodiment (not shown) it is conceivable for cylindrical part 82 to be moved back by a ratchet mechanism during rotation of disc 81.

In the embodiment 90 (fig. 10) of a device according to the present invention, the dispensing opening is covered using a foil 91 so that the powder P cannot fall out of the receiving cavity. During inhalation the foil will be lifted, whereby the powder will be drawn along. The foil is for instance fixed using a plastic part for locking thereof.

In the embodiment 95 of fig. 11, a slide 96 in which an opening 97 is arranged is moved outward during inhaling until opening 97 is situated above the cavity for the powder, so that the powder is drawn along by the inhaling airflow. With further rotation of disc 98 the slide 96 is urged back into a position closing the following cavity.

In preferred embodiment 100 (fig. 12) according to the present invention the air is drawn in via arrows E laterally above disc 102 through openings 101 and subsequently guided via arrows F in spiral form through the spiral-shaped housing over a dose of powder P. Owing

to the long air path in spiral form, the powder will in practice not leave the device 100 via the spiral-shaped path, or hardly so. In addition to the possibility of creating a long air path, the lateral suction has the advantage that the user will be unable or hardly able to cover openings 101 with one or more fingers. This embodiment is provided with seven cavities for receiving material for inhaling, for instance for daily use of medication. The diameter of the disc-like component amounts to for instance 32 mm, in contrast to the embodiment for four doses, wherein this dimension can amount to for instance 25 mm.

In the embodiment 110 (fig. 13) a component 111 provided with a number of, for instance four, blades is set into rotating movement during inhalation by the air flow as indicated with arrows G. In the space between two blades the air is guided over a cavity in which powder P is situated so that such powder can be inhaled. The device of fig. 13 can have the same dimensions as the above stated device of fig. 12.

It will be apparent that the above described preferred embodiments, particularly those of fig. 6-13, prevent powder falling out of the inhaler if it is used upside down.

The present invention is not limited to the above described preferred embodiments thereof; the rights sought are defined by the following claims, within the scope of which many modifications can be envisaged.

CLAIMS

1. Device for inhaling medication, comprising:
 - a first housing part provided with one or more cavities in which a dose of a pre-determined quantity of medication can be arranged; and
 - a second housing part which is fixed substantially non-releasably to the first housing part, wherein the first and second housing parts are movable relative to one another between a first position wherein the cavities with powdered medication are closed and a second position in which the cavity is placed into connection with an air path and the medication can be inhaled.
2. Device as claimed in claim 1, wherein a mouthpiece for inhaling the medication is provided by one component of the housing or both components together.
3. Device as claimed in claim 1 or 2, wherein the movable component is rotatable.
4. Device as claimed in claim 3, wherein the movable component is only rotatable in one direction.
5. Device as claimed in claim 1 or 4, wherein the movable component is substantially disc-shaped and provided with a central air inlet opening for admitting air and a number of receiving cavities for receiving a corresponding number of doses.
6. Device as claimed in any of the foregoing claims, provided with counting means for counting the number of doses still available.
7. Device as claimed in any of the foregoing claims, provided with a liquid-tight packaging such as a blister pack or sachet.
8. Device as claimed in any of the foregoing claims, wherein a clicking sound is audible in the second position.

9. Device as claimed in any of the claims 3-8, wherein the rotatable component is provided with corrugations or gripping surfaces.

10. Device as claimed in any of the foregoing claims, wherein the first and second housing parts are provided with respective conical parts fitting onto each other for non-releasable mutual fixing thereof.

11. Device as claimed in any of the foregoing claims, wherein the movable part is blocked in a final position wherein no further dose is available.

12. Device as claimed in any of the claims 3-11, wherein with further rotation a non-inhaled dose is closed off from the environment.

13. Device as claimed in any of the claims 2-15 12, provided with an edge on the mouthpiece.

14. Device as claimed in one or more of the claims 4-14, provided with a ratchet mechanism for allowing the movable component to rotate in only one direction.

15. Device as claimed in claim 11, 12, 13 or 14, provided with blocking means on the outside of the device for blocking the movable part in the final position.

16. Device as claimed in one or more of the foregoing claims, provided with closing means which in the rest position close off a dose and which are moved out of the closing position by inhalation in order to release the dose.

17. Device as claimed in claim 16, wherein the closing means comprise a foil.

18. Device as claimed in claim 16, wherein the closing means comprise a rotatable and slidable valve.

19. Device as claimed in one or more of the foregoing claims, wherein an air suction opening is arranged on the underside of the device.

20. Device as claimed in one or more of the foregoing claims, provided with a collecting cavity arranged in the top part of the mouthpiece for collecting

a dose of medication in upside-down position of the device.

21. Device as claimed in one or more of the foregoing claims, provided with blocking means for blocking the mutual rotating movement in upside-down position of the device.

22. Device as claimed in one or more of the foregoing claims, provided with a substantially spiral-shaped air path.

23. Device as claimed in one or more of the foregoing claims, provided with a rotatable element with blades.

24. Device as claimed in one or more of the foregoing claims, provided with one or more air inlet openings arranged in the side wall.




FIG. 1




FIG. 3

FIG. 2




FIG. 4




FIG. 5




FIG. 6




FIG. 8




FIG. 9




FIG. 7A





FIG. 7B



INTERNATIONAL SEARCH REPORT

 International Application No.
PCT/ML 99/00028

1. CLASSIFICATION OF SUBJECT MATTER

IPC 6 A61R15/00

According to International Patent Classification (IPC) or to both national classification and IPC

2. FIELD SEARCHED

Patent documents searched: abstracts only; documents full-text; documents full-text and abstracts

IPC 6 A61R

Documents inspected other than non-patent literature: in the extent that such documents are included in the field searched

Documents inspected during the international search phase of the patent process, where possible, under the same terms

3. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Number of documents, with indication, where appropriate, of the relevant passages	Reference to claim No.
X	US 4 860 740 A (KIRK WILLIAM F ET AL) 29 August 1989 see column 11, line 45 - column 12, line 19; figures 7, 8	1-3, 9, 12, 13 4, 6, 8, 11, 19, 21-24
Y	WO 97 25086 A (GLAZO GROUP LTD; ANDERSON GREGOR JOHN MCLENNAN (GB); WALKER RICHARD) 17 July 1997 see page 12, paragraph 2; figures	4, 6, 24
A	DE 38 23 535 A (RECHTS HEINRICH PROF DR ING) 18 January 1990 see column 3, line 42 - line 47	8
Y	US 5 301 666 A (LEIK COERKRAAD ET AL) 12 April 1994 see column 5, line 51 - line 61	8
Y	US 5 301 666 A (LEIK COERKRAAD ET AL) 12 April 1994 see column 5, line 51 - line 61	11
	-/-	

Further documents are listed in the continuation of item C.

Patent family documents are listed in item C.

1. General categories of cited documents:

"X" Document defining the generic state of the art which is not considered to be of particular importance

"Y" Document defining the generic state of the art which is not considered to be of particular importance

"A" Document which may have been cited on priority claims or which is cited to establish the publication date of another document or other general reason (as specified)

"E" Document which is cited to establish the publication date of another document or other general reason (as specified)

"F" Document published prior to the international search date but later than the priority date claimed

"X" Document published after the international search date or which is cited to establish the publication date of another document or other general reason (as specified)

"Y" Document published after the international search date or which is cited to establish the publication date of another document or other general reason (as specified)

"A" Document which may have been cited on priority claims or which is cited to establish the publication date of another document or other general reason (as specified)

"E" Document which is cited to establish the publication date of another document or other general reason (as specified)

"F" Document published prior to the international search date but later than the priority date claimed

Date of the international search

29 April 1999

Date of mailing of the international search report

10/05/1999

 Name and mailing address of the ISA
 European Patent Office, P.O. Box 2911, Postfach 2
 6000, 6000, 6000, 6000, 6000, 6000, 6000, 6000, 6000, 6000
 Tel: +49-69-720-4000, Fax: +49-69-720-4000, Telex: +49-69-720-4000

 Authorized officer
 Villeneuve, J-M

Form PCT/ML 99/00028 (01/01/99)

page 1 of 2

INTERNATIONAL SEARCH REPORT

 International Application No.
PCT/ML 99/00028

Category	Number of documents, with indication, where appropriate, of the relevant passages	Reference to claim No.
Y	US 5 642 727 A (DATTI PABITRA ET AL) 1 July 1997 see column 4, last paragraph; figure 4	19
Y	US 3 565 070 A (HANSON DALE B ET AL) 23 February 1971 see column 5, last paragraph - column 6, paragraph 1	21
Y	WO 94 14492 A (AMBROSIO THOMAS J; MANTHEMA SRINIVAS (US); SCHERLING CORP (US); WIL) 7 July 1994 see abstract; figure 47	22
Y	US 5 372 128 A (SHIDLEY WILLIAM H ET AL) 13 December 1994 see abstract; figure 2	23

Form PCT/ML 99/00028 (01/01/99)

page 2 of 2

INTERNATIONAL SEARCH REPORT

Information on patent family members

 International Application No.
PCT/ML 99/00028

Patent documents cited in search report	Publication date	Patent family identifier(s)	Publication date
US 4860740 A	29-08-1989	AR 226386 A	30-06-1982
		AU 554502 B	21-09-1986
		AJ 7893381 A	21-05-1992
		BE 890937 A	30-04-1982
		BR 8108854 A	21-09-1982
		CA 1169322 A	19-06-1984
		DK 293882 A, B	30-06-1982
		EP 0063599 A	03-11-1992
		FI 762540 B	30-06-1986
		GB 75358 A	13-07-1984
		IE 52783 B	02-03-1988
		JP 2037188 B	22-08-1990
		JP 57501815 T	14-10-1992
		PT 72809 A, B	01-11-1981
		WO 8201470 A	13-05-1982
		ZA 8107513 A	25-05-1983
WO 9725086 A	17-07-1997	AU 1163397 A	01-03-1997
		CA 2241880 A	17-07-1997
		CZ 9802125 A	11-11-1998
		EP 0883414 A	16-12-1998
		NO 983069 A	03-09-1998
		PL 327616 A	21-12-1998
DE 3823535 A	18-01-1990	NONE	
US 5301666 A	12-04-1994	DE 4211475 A	17-06-1993
		AT 139453 B	15-07-1996
		BR 9204987 A	15-06-1993
		CA 2084832 A	15-06-1993
		CN 1074381 A	21-07-1993
		DE 59206614 D	25-07-1996
		EP 0547429 A	23-06-1993
		FR 214757 B	25-05-1993
		IL 103908 A	16-10-1996
		JP 5245201 A	24-09-1993
		ZA 9209232 A	26-05-1993
US 5642727 A	01-07-1997	AU 6841996 A	26-02-1997
		CA 2227594 A	13-02-1997
		EP 0840631 A	13-05-1998
		WO 9704827 A	13-02-1997
US 3565070 A	23-02-1971	BE 746638 A	27-03-1970
		CH 521132 A	15-04-1972
		DE 2008769 A	03-09-1970
		DK 130391 B	17-02-1975
		FR 2037445 A	31-12-1970
		GB 1297993 A	29-11-1972
		JP 49036600 B	02-10-1974
		KL 7002237 A	01-09-1970
		SE 378969 B	22-09-1975
WO 9414492 A	07-07-1994	AT 177323 T	15-03-1999
		AU 683038 B	30-10-1997
		AU 5748794 A	19-07-1994
		CA 2152080 A	07-07-1994
		CN 1091321 A	21-03-1994

Form PCT/ML 99/00028 (01/01/99)

page 1 of 2

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No.
PCT/IL 99/00028

Parent document Class in source region	Publication date	Parent family member(s)	Publication date
WD 9414492 A		CZ 9501535 A	15-05-1996
		DE 69323897 D	15-04-1999
		EP 0674533 A	04-10-1995
		FI 952976 A	16-06-1995
		HU 71552 A, B	28-09-1996
		IL 108061 A	10-06-1997
		JP 8500756 T	30-01-1996
		RO 952429 A	18-08-1995
		RZ 259241 A	29-12-1996
		PL 309401 A	02-10-1995
		SG 52237 A	29-09-1998
		SK 80695 A	07-02-1996
		US 5829434 A	03-11-1998
		US 5687710 A	18-11-1997
		US 5740792 A	21-04-1998
		ZA 9309472 A	19-06-1995
US 5372128 A	13-12-1994	NONE	

Form PCT/IS290 (parent family member) (July 1999)